

**AKZENT**

Balm for wood

— TECHNICAL INFORMATION —

WEAR CATEGORIES PARQUET FINISHES AND OILS

AKZENT Balm for wood	BEANSPRUCHUNG		
	NORMAL	MEDIUM	HEAVY
Waterborne finishes			
AKZENT AQUA AERIS	✓ Application method: 3 x with a roller or 2 x with a trowel + 2 x with a roller = 300-360 ml/m ²	✓ Application method: 3 x with a roller or 2 x with a trowel + 2 x with a roller = 300-360 ml/m ²	
AKZENT AQUA ARGENTUM	✓ Application method: 3 x with a roller or 2 x with a trowel + 2 x with a roller = 300 ml/m ²	✓ Application method: 3 x with a roller or 2 x with a trowel + 2 x with a roller = 300 ml/m ²	✓ Application method: 3-4 x with a roller = 360-400 ml/m ²
AKZENT AQUA AURUM	✓ Application method: 3 x with a roller or 2 x with a trowel + 2 x with a roller = 300 ml/m ²	✓ Application method: 3 x with a roller or 2 x with a trowel + 2 x with a roller = 300 ml/m ²	✓ Application method: 3 x with a roller = 360 ml/m ²
Oil-based synthetic resin finishes			
AKZENT KH PRO*	✓ Application method: 2-3 x with a roller = approx. 200-300 ml/m ²	✓ Application method: 2-3 x with a roller = approx. 200-300 ml/m ²	✓ Application method: 3 x with a roller = approx. 300 ml/m ²
Oils			
AKZENT OIL IN ONE	✓ Application method: 1 x with a trowel or with a roller + polishing = approx. 20-50 ml/m ²	✓ Application method: 1 x with a trowel or with a roller + polishing = approx. 20-50 ml/m ²	✓ Application method: 1-2 x with a trowel or 1 x with a roller + polishing = approx. 20-50 ml/m ²
AKZENT OIL IN ONE COLOR	✓ Application method: 1 x with a trowel or with a roller + polish- ing = approx. 20-50 ml/m ²	✓ Application method: 1 x with a trowel or with a roller + polish- ing = approx. 20-50 ml/m ²	ⓘ Application method: 1 x with a trowel or 1 x with a roller + polishing = approx. 20-50 ml/m ² , ideally reworking with layer-forming surface treatment agents
AKZENT HARDWAX OIL	✓ Application method: 2 x with a roller = approx. 100 ml/m ²	✓ Application method: 2 x with a roller = approx. 100 ml/m ²	✓ Application method: 2 x with a roller = approx. 100 ml/m ²

✓ recommended ⓘ limited suitability

Wear categories for AKZENT parquet finishes and oils:

Normal wear: Living areas with rooms subject to normal use, e.g. bedrooms or living rooms.

Medium wear: Rooms with frequent use, e.g. children's rooms, hallways or living rooms.

Heavy wear: Rooms with very frequent use, e.g. in nurseries, schools, department stores, restaurants.

Usage information:

It is advisable to use primers for all wear categories.

Please also refer to our technical data sheets and technical information on surface treatment.

* TRGS 617 must be adhered to if, for technical reasons, products with a high solvent content are used.